

**KOMEX**

STYLOWE CIEPŁO

## DANE TECHNICZNE GRZEJNIKA AMANDA 20

wysokość	szerokość	głębokość od ściany do środka osi przyłączy	głębokość całkowita od ściany	rozstaw otworów montażowych	ciężar (kg)	pojemność (dm <sup>3</sup> )	moc [W] 55/45/20° C	moc [W] 75/65/20° C	moc [W] 90/70/20° C	poponowana moc grzałki
720	453	55-75	85-105	423	5,0	3,0	200	334	415	300
720	595	55-75	98-118	565	6,1	3,5	248	414	516	300
960	453	55-75	85-105	423	7,0	4,0	274	457	569	400
960	595	55-75	98-118	565	8,5	5,0	351	585	728	600
960	742	55-75	105-125	712	9,9	5,5	427	711	886	600
1320	453	55-75	85-105	423	9,5	5,5	371	618	770	600
1320	595	55-75	98-118	565	11,5	6,5	475	791	985	800
1320	742	55-75	105-125	712	13,5	7,5	578	964	1200	800
1680	453	55-75	85-105	423	12,0	7,0	480	800	996	600
1680	595	55-75	98-118	565	14,5	8,5	597	995	1239	800
1680	742	55-75	105-125	712	17,0	10,0	728	1213	1510	1000
1880	453	55-75	85-105	423	13,2	8,0	509	848	1056	800
1880	595	55-75	98-118	565	16,0	9,5	650	1084	1350	1000
1880	742	55-75	105-125	712	18,7	10,5	793	1321	1645	1000