

KOMEX

STYLowe CIEPŁO

DANE TECHNICZNE GRZEJNIKA ELENA POJEDYNCZA

wysokość	szerokość	liczba elementów	głębokość od ściany do środka osi przyłączy	głębokość całkowita od ściany	rozstaw otworów montażowych	ciężar (kg)	pojemność (dm ³)	moc [W] 55/45/20° C	moc [W] 75/65/20° C	moc [W] 90/70/20° C	proponowana moc grzałki
1000	300	10	41	88	950	9,7	3,5	262	436	546	300
1000	390	13	41	88	950	12,6	4,5	340	567	710	600
1000	450	15	41	88	950	14,4	5,0	392	654	820	600
1000	540	18	41	88	950	17,4	6,0	471	785	984	600
1000	600	20	41	88	950	19,4	6,5	523	872	1093	800
1500	300	10	41	88	1450	14,2	5,0	384	640	802	600
1500	390	13	41	88	1450	18,4	6,5	499	831	1042	800
1500	450	15	41	88	1450	21,2	7,5	575	959	1203	800
1500	540	18	41	88	1450	25,5	8,5	691	1151	1443	1000
1500	600	20	41	88	1450	28,3	9,5	767	1279	1603	1000
1800	300	10	41	88	1750	16,9	6,0	457	762	955	600
1800	390	13	41	88	1750	21,9	7,5	594	990	1241	800
1800	450	15	41	88	1750	25,3	8,5	686	1143	1432	1000
1800	540	18	41	88	1750	30,3	10,5	823	1371	1719	1000
1800	600	20	41	88	1750	33,7	11,5	914	1523	1910	1000
2000	300	10	41	88	1950	18,7	6,5	506	843	1057	600
2000	390	13	41	88	1950	24,3	8,0	658	1096	1374	1000
2000	450	15	41	88	1950	28,0	9,5	759	1265	1585	1000
2000	540	18	41	88	1950	33,6	11,5	911	1518	1902	1000
2000	600	20	41	88	1950	37,3	12,5	1012	1686	2114	1000