

KOMEX

STYLowe CIEPŁO

DANE TECHNICZNE GRZEJNIKA RENE Z OSŁONĄ SZKLANĄ POJEDYNCZY

wysokość	szerokość	liczba elementów	głębokość od ściany do środka osi przyłączy	głębokość całkowita od ściany	rozstaw otworów montażowych	ciężar (kg)	pojemność (dm ³)	moc [W] 55/45/20° C	moc [W] 75/65/20° C	moc [W] 90/70/20° C	proponowana moc grzałki
600	352	6	60	118	550	7,9	3,5	155	259	325	300
600	410	7	60	118	550	8,6	4,0	181	302	379	300
600	468	8	60	118	550	12,6	4,5	207	345	433	300
600	526	9	60	118	550	13,8	5,0	233	389	487	300
600	584	10	60	118	550	15,5	5,5	259	432	541	600
600	642	11	60	118	550	17,2	6,0	285	475	595	600
1000	352	6	60	118	950	11,5	5,5	245	409	513	600
1000	410	7	60	118	950	13,6	6,0	287	478	599	600
1000	468	8	60	118	950	20,4	7,0	328	546	684	600
1000	526	9	60	118	950	22,5	8,0	368	614	770	600
1000	584	10	60	118	950	25,2	9,0	409	682	855	600
1000	642	11	60	118	950	27,8	9,5	450	750	940	800
1500	352	6	60	118	1450	17,0	6,5	358	597	749	600
1500	410	7	60	118	1450	19,0	8,0	418	697	873	800
1500	468	8	60	118	1450	22,5	10,0	478	796	998	800
1500	526	9	60	118	1450	33,2	11,5	538	896	1123	800
1500	584	10	60	118	1450	37,0	13,0	597	995	1247	1000
1500	642	11	60	118	1450	40,8	14,0	657	1095	1372	1000
1800	352	6	60	118	1750	20,0	6,0	426	710	890	800
1800	410	7	60	118	1750	23,0	7,5	497	828	1038	800
1800	468	8	60	118	1750	35,3	12,0	568	946	1186	1000
1800	526	9	60	118	1750	40,0	13,5	639	1065	1335	1000
1800	584	10	60	118	1750	44,0	15,0	710	1183	1483	1000
1800	642	11	60	118	1750	48,5	16,5	781	1301	1631	1000