

**KOMEX**

STYLÓWE CIEPŁO

## DANE TECHNICZNE GRZEJNIKA SUPRA

wysokość	szerokość	liczba elementów	głębokość od ściany do środka osi przyłączy	głębokość całkowita od ściany	rozstaw otworów montażowych	ciężar (kg)	pojemność (dm <sup>3</sup> )	moc [W] 55/45/20° C	moc [W] 75/65/20° C	moc [W] 90/70/20 °C	proponowana moc grzałki
600	310	8	45	90	500	6,9	1,5	158	264	333	-
600	390	10	45	90	500	8,6	1,5	198	330	417	-
600	470	12	45	90	500	10,4	2,0	238	396	500	-
600	550	14	45	90	500	12,1	2,5	278	463	583	-
600	630	16	45	90	500	13,8	3,0	317	529	667	-
600	710	18	45	90	500	15,5	3,0	357	595	750	-
900	310	8	45	90	800	10,0	2,0	232	387	488	-
900	390	10	45	90	800	12,5	2,5	290	483	610	-
900	470	12	45	90	800	15,0	3,0	348	580	732	-
900	550	14	45	90	800	17,5	3,0	406	677	854	-
900	630	16	45	90	800	20,0	3,5	464	774	976	-
900	710	18	45	90	800	22,5	4,0	523	871	1098	-
1200	310	8	45	90	1100	13,1	2,5	305	509	642	-
1200	390	10	45	90	1100	16,4	3,0	382	636	803	-
1200	470	12	45	90	1100	19,7	3,5	458	764	964	-
1200	550	14	45	90	1100	23,0	4,0	535	891	1124	-
1200	630	16	45	90	1100	26,3	4,5	611	1019	1285	-
1200	710	18	45	90	1100	29,5	5,0	688	1146	1446	-
1500	310	8	45	90	1400	16,2	3,0	379	632	797	-
1500	390	10	45	90	1400	20,3	3,5	474	790	996	-
1500	470	12	45	90	1400	24,3	4,0	569	948	1196	-
1500	550	14	45	90	1400	28,4	5,0	664	1106	1395	-
1500	630	16	45	90	1400	32,5	5,5	758	1264	1594	-
1500	710	18	45	90	1400	26,5	6,0	853	1422	1794	-
1800	310	8	45	90	1700	9,3	3,0	452	754	951	-
1800	390	10	45	90	1700	24,2	4,0	566	943	1189	-
1800	470	12	45	90	1700	29,0	5,0	679	1131	1427	-
1800	550	14	45	90	1700	33,8	5,5	792	1320	1665	-
1800	630	16	45	90	1700	38,7	6,5	905	1509	1903	-
1800	710	18	45	90	1700	43,5	7,0	1019	1698	2141	-