

KOMEX

STYLowe CIEPŁO

DANE TECHNICZNE GRZEJNIKA VICTORIA PODWÓJNA Z OSŁONĄ SZKLANĄ

wysokość	szerokość	ilość elementów	głębokość od ściany do środka osi przyłączy	głębokość całkowita od ściany	rozstaw otworów montażowych	ciężar (kg)	pojemność (dm ³)	moc [W] 55/45/20° C	moc [W] 75/65/20° C	moc [W] 90/70/20° C	proponowana moc grzałki
600	445	6+6	55	104-108	550	16,9	3,5	380	634	795	-
600	595	8+8	55	104-108	550	22,2	4,5	494	823	1032	-
600	745	10+10	55	104-108	550	28,0	5,5	605	1009	1264	-
600	895	12+12	55	104-108	550	32,8	6,5	715	1191	1493	-
600	1045	14+14	55	104-108	550	38,2	7,5	821	1369	1716	-
1000	445	6+6	55	104-108	950	27,3	5,0	586	977	1225	-
1000	595	8+8	55	104-108	950	36,4	6,5	761	1269	1590	-
1000	745	10+10	55	104-108	950	45,5	8,0	923	1538	1928	-
1000	895	12+12	55	104-108	950	54,4	10,0	1092	1820	2281	-
1000	1045	14+14	55	104-108	950	63,3	12,0	1264	2106	2639	-
1500	445	6+6	55	104-108	1450	41,0	7,0	844	1406	1762	-
1500	595	8+8	55	104-108	1450	53,9	9,5	1076	1794	2248	-
1500	745	10+10	55	104-108	1450	67,9	12,0	1326	2210	2769	-
1500	895	12+12	55	104-108	1450	76,4	13,0	1560	2600	3258	-
1500	1045	14+14	55	104-108	1450	85,9	14,5	1802	3003	3763	-
1800	445	6+6	55	104-108	1750	48,1	8,5	980	1633	2047	-
1800	520	7+7	55	104-108	1750	56,0	10,0	1111	1851	2320	-
1800	595	8+8	55	104-108	1750	64,8	11,0	1270	2116	2652	-
1800	745	10+10	55	104-108	1750	80,5	14,0	1551	2585	3240	-
1800	895	12+12	55	104-108	1750	97,2	15,5	1840	3067	3843	-
1800	1045	14+14	55	104-108	1750	112,6	17,0	2078	3464	4341	-
2000	445	6+6	55	104-108	1950	53,6	9,5	1052	1753	2197	-
2000	595	8+8	55	104-108	1950	71,5	12,5	1376	2294	2875	-
2000	745	10+10	55	104-108	1950	89,4	15,5	1692	2820	3534	-
2000	895	12+12	55	104-108	1950	107,3	17,5	1978	3296	4130	-
2000	1045	14+14	55	104-108	1950	124,8	19,0	2306	3844	4817	-