

KOMEX

STYLOWE CIEPŁO

DANE TECHNICZNE GRZEJNIKA VICTORIA POJEDYNCZA

wysokość	szerokość	ilość elementów	głębokość od ściany do środka osi przyłączy	głębokość całkowita od ściany	rozstaw otworów montażowych	ciężar (kg)	pojemność (dm ³)	moc [W] 55/45/20° C	moc [W] 75/65/20° C	moc [W] 90/70/20° C	proponowana moc grzałki
600	295	4	44	74	550	4,2	1.5	137	228	285	300
600	445	6	44	74	550	6.3	2.0	211	352	441	300
600	595	8	44	74	550	8.3	2.5	274	457	573	300
600	745	10	44	74	550	10.4	3.0	336	560	702	600
600	895	12	44	74	550	12.4	4.0	397	661	828	600
600	1045	14	44	74	550	14.5	4.5	456	760	953	600
1000	295	4	44	74	950	6.5	2.0	206	344	432	300
1000	445	6	44	74	950	9.7	3.0	320	534	669	300
1000	595	8	44	74	950	12.9	3.5	416	693	869	600
1000	745	10	44	74	950	16.1	4.5	509	849	1065	800
1000	895	12	44	74	950	19.3	5.5	602	1003	1257	1000
1000	1045	14	44	74	950	22.6	7.0	692	1154	1446	1000
1500	295	4	44	74	1450	9.4	3.0	291	485	608	300
1500	445	6	44	74	1450	15.6	3.5	452	753	944	600
1500	595	8	44	74	1450	20.8	5.0	587	978	1227	800
1500	745	10	44	74	1450	25.9	6.0	719	1198	1503	1000
1500	895	12	44	74	1450	31.0	7.0	848	1414	1774	-
1500	1045	14	44	74	1450	36.2	8.0	976	1627	2040	-
1800	295	4	44	74	1750	11.1	3.0	340	567	711	600
1800	445	6	44	74	1750	18.5	4.0	529	881	1105	800
1800	595	8	44	74	1750	24.6	5.5	687	1145	1436	1000
1800	745	10	44	74	1750	30.8	6.8	842	1403	1759	1000
1800	895	12	44	74	1750	36.9	8.2	993	1655	2076	-
1800	1045	14	44	74	1750	43.2	9.5	1143	1905	2388	-
2000	295	4	44	74	1950	12.3	3.5	373	622	779	600
2000	445	6	44	74	1950	20.5	4.5	580	966	1211	800
2000	595	8	44	74	1950	27.3	6.1	753	1255	1573	1000
2000	745	10	44	74	1950	34.2	7.5	922	1537	1927	1000
2000	895	12	44	74	1950	50.0	9.1	1088	1814	2275	-
2000	1045	14	44	74	1950	54.4	10.2	1252	2087	2617	-