

KOMEX

STYLowe CIEPŁO

DANE TECHNICZNE GRZEJNIKA VICTORIA POJEDYNCZA Z OSŁONĄ SZKLANĄ

wysokość	szerokość	ilość elementów	głębokość od ściany do środka osi przyłączy	głębokość całkowita od ściany	rozstaw otworów montażowych	ciężar (kg)	pojemność (dm ³)	moc [W] 55/45/20° C	moc [W] 75/65/20° C	moc [W] 90/70/20° C	proponowana moc grzałki
600	445	6	44	92-96	550	11,8	2,0	211	352	441	300
600	595	8	44	92-96	550	15,3	2,5	274	457	573	300
600	745	10	44	92-96	550	19,4	3,0	336	560	702	600
600	895	12	44	92-96	550	23,4	4,0	397	661	828	600
600	1045	14	44	92-96	550	27,0	4,5	456	760	953	600
1000	445	6	44	92-96	950	18,7	3,0	320	534	669	300
1000	595	8	44	92-96	950	24,9	3,5	416	693	869	300
1000	745	10	44	92-96	950	31,1	4,5	509	849	1065	600
1000	895	12	44	92-96	950	37,3	5,5	602	1003	1257	800
1000	1045	14	44	92-96	950	43,6	7,0	692	1154	1446	1000
1500	445	6	44	92-96	1450	29,6	3,5	452	753	944	300
1500	595	8	44	92-96	1450	38,8	5,0	587	978	1227	600
1500	745	10	44	92-96	1450	48,9	6,0	719	1198	1503	800
1500	895	12	44	92-96	1450	58,0	7,0	848	1414	1774	-
1500	1045	14	44	92-96	1450	68,2	8,0	976	1627	2040	-
1800	445	6	44	92-96	1750	34,5	4,0	529	881	1105	600
1800	520	7	44	92-96	1750	41,0	4,5	616	1027	1289	800
1800	595	8	44	92-96	1750	46,6	5,5	687	1145	1436	-
1800	745	10	44	92-96	1750	57,8	6,8	842	1403	1759	-
1800	895	12	44	92-96	1750	69,9	8,2	993	1655	2076	-
1800	1045	14	44	92-96	1750	81,2	9,5	1143	1905	2388	600
2000	445	6	44	92-96	1950	38,5	4,5	580	966	1211	800
2000	595	8	44	92-96	1950	51,3	6,1	753	1255	1573	1000
2000	745	10	44	92-96	1950	64,2	7,5	922	1537	1927	-
2000	895	12	44	92-96	1950	86,0	9,1	1088	1814	2275	-
2000	1045	14	44	92-96	1950	96,4	10,2	1252	2087	2617	-